



O-RAN End-to-End Energy **Efficiency Testing Framework**

Marcin Hoffmann, Marcin Dryjański, Adrian Kliks

All things wireless

Motivation



Challenges in O-RAN E2E Energy Efficiency Testing






Multiple hardware and software vendors offer energy-saving solutions that are hard to compare – a lack of unified test definitions and scenarios



Various organizations put effort into the energy efficiency testing, e.g., ETSI, 3GPP, O-RAN ALLIANCE, NGNM, TIP – yet their work cover different aspects of E2E EE Testing






There is a demand to combine the current standardization efforts into the unified O-RAN E2E EE Testing Framework that would provide common procedures to evaluate energy efficiency of network components, like O-CU/O-DU/O-RU, and xApps/rApps





ETSI - Configuration





Integrated BS model (example)
[ETSI_2027061_TS]

Distributed BS model (example) [ETSI_2027061_TS]



ETSI – Static/Dynamic Load Measurements



Utilize, and extend existing ETSI procedures

Power supply requirements

Environmental conditions

Static Load measurements


Dynamic Load measurements

Measurement reports

Combine the ETSI-defined measurements and procedures with 3GPP, and O-RAN ALLIANCE to create a "component-level EE testing framework"

Table 1 BS environmental conditions [ETSI_103786_TS]

Condition	Minimum	Maximum
Barometric pressure	86 kPa (860 mbar)	106 kPa (1 060 mbar)
Relative Humidity	20 %	85 %
Vibration	Negligible	
Temperature	+25 °C and +40 °C	
Temperature accuracy	±2 °C	





O-RAN Test and Measurement Aspects for NES



TIFG and SuFG

(Energy Measurement Analysis Report)

O-RAN End-to-end Test Specification 7.0

O-RAN.TIFG.TS.E2E-Test.0-R004-v07.00

June 2025

Technical

R004

Specification

DOWNLOAD

This test specification is focused on validating the end-to-end system functionality, performance, and key features of the O-RAN system as a black box. The changes from previous version: • DTAG-0004: Alignment with latest TS template • DTAG-0006: Removed 3GPP-specific termininology (e.g. gNB) when referring to "O-RAN system"



O-RAN.SuFG.TR.NES-Analysis-R004-v01.01

Technical Report

Introduction

Open RAN energy management is a key sustainability objective shared by mobile operators worldwide, aiming to scale Open RAN technology for commercial deployments and expedite its development. As part of broader industry goals, leading operators have highlighted energy efficiency as critical to Open RAN's success, underscoring their commitment to advancing sustainable telecommunications infrastructure. To achieve meaningful energy savings, while ensuring reliable performance, the telecom industry requires a standardized approach not only to save energy but also to evaluate, test, measure, and monitor energy consumption in Open RAN deployments. This Technical Report (TR) analyzes operator requirements related to energy consumption measurements and energy efficiency KPIs and identifies gaps within O-RAN ALLIANCE specifications to align with these industry-wide priorities

O-Cloud Energy Measurements

Foundational Requirements for O-Cloud...... Energy consumption KPIs at hardware level..... Energy consumption KPIs at Workload level Granular Energy Measurement Reporting and Control

O-RU Energy Measurements

Foundational Requirement for O-RU...... O-RU Energy measurements reporting

O-CU & O-DU Energy related Measurements
Foundational requirements for O-CU / O-DU

SMO Automations

Foundational requirements on SMO Automations........... SMO Capabilities related to Energy Measurements....

O-DU & O-CU Energy measurements reporting

Gap analysis for Energy measurements

WG6 has already specified a generic framework for PM reporting and is currently working on stage 3 specifications for O2 PM. In the ongoing study on O-Cloud Energy Savings WG6 has provided an initial analysis for power and energy consumption metrics of infrastructure

SuFG TG2 identified following gaps:

- WG6 has not defined a data model for O2 PM measurements. Currently, only a framework exists for transporting supplier-proprietary data elements, which are specified within supplier-specific dictionaries.
- Discussions within WG6 have revealed differing opinions regarding the exposure of hardware and component-level measurements to the SMO, resulting in a lack of consensus on this issue.
- The O-RAN ALLIANCE has not yet established a clear definition or framework for measuring hardware energy efficiency, such as computing performance per watt (Compute/Watt).

It is important to note that all current work in WG6 is still at the study level, and there have been no normative discussions on power or energy measurements thus far.

The ongoing Study on O-Cloud Energy Savings, now in version O-RAN.WG6.O-Cloud ES-v02.00 [i.5], provides a comprehensive analysis of power and energy consumption metrics at the infrastructure level in clause 6.

The ES technical report [i.3] have identified several KPIs and measurement methodologies for power/energy consumption, and efficiency at various levels within the O-Cloud infrastructure.

- O-Cloud Resource Power Consumption Metrics: These metrics include PowerCapacity, PowerConsumed, AveragePowerConsumed, MaxPowerConsumed, and MinPowerConsumed. These measurements apply to relevant O-Cloud resources, capturing the power dynamics over a specified interval.
- O-Cloud Node Energy Consumption Metrics: New metrics such as ECnode, core (total energy consumption of CPU cores), ECnode, uncore (uncore components like caches and memory controllers), ECnode, dram (DRAM energy), and others are introduced to monitor energy consumption across different components of the O-Cloud nodes.
- Container Energy Consumption: WG6 introduces metrics at the container level, such as ECcontainer, total (total energy consumption within a container), ECcontainer, core (energy used by CPU cores within a container), and other relevant metrics to track energy usage at the container level.


Summary of Standarization Efforts



Documents	Scope	What is missing?
ETSI	 defines metrics and measurements for EC/EE of a base station provides models for BSs and requirements for measurement equipment describes standardized test setups and procedures for power measurements (static and dynamic) for a single base station standardized reports from the measurements good starting point for O-RAN extension 	 lack O-RAN context and architecture, e.g. 7.2 split lack of scenarios/configurations for large-scale network power measurements missing procedures for testing mobile networks with VNF, e.g., virtual CU/DU QoS in EE definitions
ЗGPР	 frequently refers to ETSI regarding Energy Efficiency/power consumption defines reference scenarios, and models for system-level simulations demand on measurement of VNFs' EE/PC EE evaluation based on multiple scenarios: MBB, URLLC, mMTC/Rural, urban 	 lack of O-RAN context lack of procedures for E2E EE testing EE/Power consumption KPIs are not available per HW unit or VNF most part of the material referring to EE/EC is from TRs, not TS, i.e., not normative
NGMN	 Cloud vs Physical deployment for a mobile network presents aspects relevant to cloud-type/environment measurements metering servers, storage, and network components solutions for VMN/CNF power measurement optimization of RAN deployment points gaps/missing elements between the O-RAN and cloud aspects 	 missing O-RAN aspects gathers different aspects, but does not fill the gap between the cloud itself and the network not a specification
O-RAN	 related directly to O-RAN aspects defines NES methods, metrics, and requirements associated with the O-RU (COOS and RCR) (quite mature) concepts, requirements, and use cases optimizing for O-Cloud resources (ORES) along with metrics (early stage) test procedure, test equipment definition, test setup and configuration, test criteria for E2E testing for O-RAN ES (COOS) 	 different documents for different parts of the system (treating separately O-Cloud from COOS, RCR, ASM) test specs only for COOS rApp (early stage) several options for measurements and KPIs (not all are implemented in practice) missing large-scale testing scenarios for xApp/rApp evaluation
TIP	 a use case, being a framework for a method of reducing EC requirements, configuration, measurements, goal, interface requirements, 	 not related to testing only for a single use case and very specific only generic parameters

White paper





White paper QR code



https://www.i14y-lab.com/article/i14y-lab-energy-efficiency-testing-framework-white-paper




Overall Framework Considerations



O-RAN E2E Energy Efficiency Testing Framework






₹114y LAB rimedolabs.com


Different Views on E2E Energy Efficiency Testing




Component-level measurements for EE




Deployment view for EE testing



Global/feature based testing for EE




Multi-link/wide network EE testing





Information Exchange and Data Modeling






Test of a network E2E full-stack, with a single gNB:

- Measure power consumption of various hardware components, e.g., CU/DU/RU/RIC
- Utilize either real, emulated UE or dummy load
- Produce power consumption models for simulations
- Utilize previously measured data to create power consumption models of different vendors

Utilize power consumption model for the large-scale simulation setup

Global/feature based testing for EE



Large scale
Simulated RAN

Simulation of a large scale network:

- Test EE/ES provided by xApps/rApps
- Test xApps/rApps signalling overhead
- Test different RICs, e.g., their computational capability, delay between RAN and xApps/rApps




Component Level Measurement of EE



The Goal of the Framework




Component-level measurements for EE




Deployment Options







Power Consumption Measurement Points










The Gap Between Kepler and Redfish










Redfish measure power Of all hardware layer while Kepler only able to measure power Of selected Pods. As offset, we could see around 83 watt used for another Pods while CU+DU was not running. Also, we observed that around 92 watt difference is between Redfish and Kepler.

O-RAN Global PlugFest Fall 2024

Energey Consumption Measurement in IS-Wireless & Benetel E2E Setup

Date: 2024-10-30



Results of the tests in i14ylab showed a gap between Kepler and Redfish.



The Traffic Profiles





ETSI static load

	Low load	Medium load	Busy hour load
Duration/day	t _{low}	t _{med}	t_{BH}
Default value	6 hours	10 hours	8 hours

- Basic measurement for 10%, 30%, 50% and full load
- To obtain better power consumption profile better granularity required
- E.g., from 0 to full load with step of 10%


ETSI dynamic load





- More scenarios
- More advanced, requires UE emulators/real UE

Real-world data



- Requires operator data
- Post-processing is needed to establish per UE traffic
- Can provide a real-world evaluation scenarios under traffic variations
- UE emulators + postprocessed data



The Measurement Outcome




Fit the results of the measurement to the parameters of 3GPP TR 38.864 Power Consumption Model

- The 3GPP PC model can scaled concerning the:
 - number of used physical antenna elements, or TX/RX RUs
 - occupied BW/RBs for DL and/or UL in a slot/symbol in one CC
 - number of CCs in CA
 - number of TRPs
 - PSD or transmit power
 - number of DL and/or UL symbols occupied within a slot.
- The BS power consumption for both DL and UL consists of a static and dynamic term, e.g.,

$$P^{DL} = P_{static}^{DL} + P_{dynamic}^{DL}$$

Initial steps:

- Perform measurement (either static or dynamic) under different:
 - 1. Number of antenna elements
 - 2. Occupied BW/RBs
 - 3. number of CCs in CA
 - 4. number of TRPs
 - 5. PSD or transmit power
 - 6. number of DL and/or UL symbols occupied within a slot
- 2. Collect power consumption and load statistics
- 3. Fit the model parameters for various components, O-RU, O-DU, O-CU, etc.



Additional challenges:


- How to define a set of QoS metrics?
- How does power consumption depend on the setup, e.g., is it different for DU while employing various RU/CU?
- How power consumption scales with UE number?


Measuring Power Consumption in a Virtualized Environment





Deployment Option for Energy Measurements












Power Consumption Measurement Tools






Measurement Points Definition for Power



Consumption










the whole server (Electric socket)

PC Measuremets - Configuration and Evaluation

Redfish








PC Measurements – Kepler vs Electric Socket



- Are both measurement types needed for reliable testing (i.e., Kepler and Socketbased)?
- Is there a specific function that binds measurement types so that we can measure one and estimate the other?



PC Measurements – Hardware Test Setups



	Dell R750 (enterprise grade server stored in i14y Lab's rack)	Lenovo Legion 5 15ARH05 (consumer grade laptop)
CPU	2 x Intel Xeon Gold 6330N-2.2GHz (28 cores)	AMD Ryzen 7 4800H with Radeon Graphics 2.90 GHz (8 cores)
RAM	512 GB, 3200Mhz	32 GB, 3200Mhz
DISK	2xSSD 1.5TB	SSD 512GB
NIC	1 x 2-port 1GbE BCM5720 1 x 4-port 1 GbE Intel I350 4 x Intel XXV810 2-port 25GbE	1 x 1-port 1 GbE Wi-Fi 6 (802.11 a/b/g/n/ac/ax)
os	Ubuntu 20.04.6 LTS	Ubuntu 22.04.5 LTS

Actual Hardware





Power Measurement at Electric Socket

GUDE Electric Socket



Shelly Smart Electric Socket



Power Consumption Measurements Collection

=== TEST 1 - LOAD 60 - continous ===



```
> Starting stress-ng at 112 CORES and 60% CPU load for 60s
>> Collect cpu usage for 60s...
>>> Starting mpstat: Interval 1, Repetitions: 60
>> Collect RAM usage for 60s...
>> Collect data from redfish for 60s...
stress-ng: info: [792236] dispatching hogs: 112 cpu
                                                                                                                                                                                                                                                                                                       Gathering measurements from Kepler,
>> Collect data from gude for 60s...
stress-ng: info: [792236] successful run completed in 60.56s (1 min, 0.56 secs)
                                                                                                                                                                                                                                                                                                                   Redfish, and Electric Socket at the
> Collect prometheus metric - kepler node cpu active joules total from range 2025-08-28 09:12:12.036145 - 2025-08-28 09:13:12.632409
> Collect prometheus metric - kepler node cpu active watts from range 2025-08-28 09:12:12.036145 - 2025-08-28 09:13:12.632409
> Collect prometheus metric - kepler node cpu idle joules total from range 2025-08-28 09:12:12.036145 - 2025-08-28 09:13:12.632409
                                                                                                                                                                                                                                                                                                                                                                        same time
 > Collect prometheus metric - kepler node_cpu_idle_watts from range 2025-08-28 09:12:12.036145 - 2025-08-28 09:13:12.632409
   Collect prometheus metric - kepler node cpu joules total from range 2025-08-28 09:12:12.036145 - 2025-08-28 09:13:12.632409
   Collect prometheus metric - kepler node cpu watts from range 2025-08-28 09:12:12.036145 - 2025-08-28 09:13:12.632409
 > Collect prometheus metric - kepler node cpu usage ratio from range 2025-08-28 09:12:12.036145 - 2025-08-28 09:13:12.632409
 === TEST 1 - LOAD 60 - switching ===
 > Starting stress-ng-switching for load 1: 100%, load 2: 0%, switching time 1: 6.0s, switching time 2: 4.0s, cycles: 6
> Starting stress-ng at 112 CORES and 100% CPU load for 6.0s
>> Collect cpu usage for 60s...
                                                                                                                                  Context: kubernetes-admin@kubernetes
                                                                                                                                  Cluster: kubernetes
>>> Starting mpstat: Interval 1, Repetitions: 60
                                                                                                                                 User: kubernetes-admin
                                                                                                                                                                                                                    <2> 1m
>> Collect RAM usage for 60s...
                                                                                                                                 K9s Rev: v0.26.6 $ v0.50.9
                                                                                                                                 K8s Rev: v1.27.16
stress-ng: info: [816465] dispatching hogs: 112 cpu
>> Collect data from redfish for 60s...
>> Collect data from gude for 60s...
stress-ng: info: [816465] successful run completed in 6.27s
                                                                                                                                    time=2025-08-28T09:16:26.679Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource=tracker resource=Process id
                                                                                                                                    time=2025-08-28T09:16:26.679Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker resource=Process id
> Starting stress-ng at 112 CORES and 0% CPU load for 4.0s
                                                                                                                                    time=2025-08-28T09:16:26.679Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker resource=Process in
stress-ng: info: [818155] dispatching hogs: 112 cpu
                                                                                                                                    time=2025-08-28T09:16:26.679Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker resource=Process ic
                                                                                                                                    stress-ng: info: [818155] successful run completed in 4.01s
                                                                                                                                   time=2025-08-28T09:16:26.679Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker resource=Process in time=2025-08-28T09:16:26.679Z level=DEBUG source=internal/monitor/terminated_resource_tracker resource=Process in the contract of the con
> Starting stress-ng at 112 CORES and 100% CPU load for 6.0s
                                                                                                                                    time=2025-08-28T09:16:26.679Z level=DEBUG source=internal/monitor/terminated resource tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker
stress-ng: info: [819706] dispatching hogs: 112 cpu
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated resource tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-track
stress-ng: info: [819706] successful run completed in 6.29s
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated resource tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker.go:103 msg="Filtering" out terminated resource with low energy service=monitor service=terminated-resource-tracker.go:103 msg="Filtering" out terminated resource with low energy service=monitor service=terminated resource-tracker.go:103 msg="Filtering" out terminated resource with low energy service=monitor service=terminated resource-tracker.go:103 msg="Filtering" out terminated resource with low energy service=monitor service=terminated resource tracker.go:103 msg="Filtering" out terminated resource with low energy service=monitor service=terminated resource-tracker.go:103 msg="Filtering" out terminated resource tracker.go:103 msg="Filtering" out terminated resource track
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=termin
 > Starting stress-ng at 112 CORES and 0% CPU load for 4.0s
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy"
stress-ng: info: [821541] dispatching hogs: 112 cpu
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy
stress-ng: info: [821541] successful run completed in 4.02s
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker
> Starting stress-ng at 112 CORES and 100% CPU load for 6.0s
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracke
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker
stress-ng: info: [823599] dispatching hogs: 112 cpu
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker
stress-ng: info: [823599] successful run completed in 6.33s
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker.go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker resource=Process i
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated resource tracker go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker resource=Process i
> Starting stress-ng at 112 CORES and 0% CPU load for 4.0s
                                                                                                                                    time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/terminated_resource_tracker_go:103 msg="Filtering out terminated resource with low energy" service=monitor service=terminated-resource-tracker resource=Process id time=2025-08-28T09:16:26.680Z level=DEBUG source=internal/monitor/process.go:105 msg="Calculating Process power" service=monitor node.cpu.time=15.07999999506803 running=2077
stress-ng: info: [825220] dispatching hogs: 112 cpu
stress-ng: info: [825220] successful run completed in 4.01s
                                                                                                                                    time=2025-08-28T09:16:26.683Z level=DEBUG source=internal/monitor/container.go:74 msg="Clearing terminated containers after export" service=monitor
 > Starting stress-ng at 112 CORES and 100% CPU load for 6.0s
 stress-ng: info: [826651] dispatching hogs: 112 cpu
                                                                                                                                    time=2025-08-28T09:16:26.683Z level=DEBUG source=internal/monitor/container.go:147 mšg="snapshot updated for containers" service=monitor running=8 terminated=0
stress-ng: info: [826651] successful run completed in 6.27s
                                                                                                                                    time=2025-08-28T09:16:26.683Z level=DEBUG source=internal/monitor/vm.go:49 msg="Clearing terminated VMs after export" service=monitor
                                                                                                                                    time=2025-08-28T09:16:26.683Z level=DEBUG source=internal/monitor/vm.go:56 msg="Processing terminated VMs" service=monitor terminated=0
> Starting stress-ng at 112 CORES and 0% CPU load for 4.0s
                                                                                                                                    time=2025-08-28T09:16:26.683Z level=DEBUG source=internal/monitor/vm.go:69 msg="Calculating VM power" service=monitor node.cpu.time=15.079999999506803 running=0
stress-ng: info: [828481] dispatching hogs: 112 cpu
                                                                                                                                    time=2025-08-28T09:16:26.683Z level=DEBUG source=internal/monitor/vm.go:115 msg="snapshot updated for VMs" service=monitor running=0 terminated=0
                                                                                                                                   time=202-08-2099:10:20.0832 tevel-obbod source=internal/monitor/mpd.go:18 mag=sinsterplated to wis = service=monitor intimated=0
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/pod.go:49 mag="Clearing terminated pods" service=monitor terminated=0
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/pod.go:71 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/pod.go:71 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=Obbod source=internal/monitor.go:157 mag="No running pods found, skipping pod power calculation" service=monitor
time=2025-08-20109:16:26.6832 level=20109:16:26.6832 level=20109:16:26.6832 level=20109:16:26.6832 level=20109:26.6832 level=20109:26.6832 level=20109:26.6832 level=20109:26.6832 level=20109:26.6832 level=20109:26.6832 level=20109:26.683
stress-ng: info: [828481] successful run completed in 4.02s
> Starting stress-ng at 112 CORES and 100% CPU load for 6.0s
stress-ng: info: [829879] dispatching hogs: 112 cpu
                                                                                                                                  time=2025-08-28109:16:26.6832 Level=INEBUG Source=Internal/monitor/monitor.go:344 msg="ferrenshapsnot service=monitor processes=20// containers=8 vms=0 pods=0 terminated time=2025-08-28109:16:26.6832 Level=INEBUG source=prometheus/collector/power_collector.go:308 msg="No processes to export metrics" collector=power state=terminated time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:308 msg="No containers to export metrics for" collector=power state=terminated time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:302 msg="No vms to export metrics for" collector=power state=terminated time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:302 msg="No vms to export metrics for" collector=power state=terminated time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:411 msg="No pods to export metrics" collector=power state=running time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:411 msg="No pods to export metrics" collector=power state=running time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:212 msg="No pods to export metrics" collector=power state=running time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:212 msg="No pods to export metrics" collector=power state=running time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:212 msg="No pods to export metrics" collector=power state=running time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:212 msg="No pods to export metrics" collector=power state=running time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:212 msg="No pods to export metrics" collector=power state=running time=2025-08-28109:16:26.7202 Level=DEBUG source=prometheus/collector/power_collector.go:212 msg="No pods to export metrics" collector=po
stress-ng: info: [829879] successful run completed in 6.25s
 > Starting stress-ng at 112 CORES and 0% CPU load for 4.0s
 stress-ng: info: [831419] dispatching hogs: 112 cpu
 stress-ng: info: [831419] successful run completed in 4.02s
 > Starting stress-ng at 112 CORES and 100% CPU load for 6.0s
```


CPU Load - Enforced vs Measured





Difference Between Target and Measured CPU Load (in Percentage Points) (n=5) 15.0 10.0 7.5 10.0 2.5 10.0 10

Lenovo Legion 5 15ARH05




Some anomalies were observed for the laptop measurement, but their effect is minimal

The difference between the CPU load enforced by the stress-test application and the actual CPU load is related to other processes



Static CPU Load - Kepler, Redfish, and Electric Socket








Static CPU Load - Offset Between Kepler, Redfish,



and Electric Socket




In both cases, the **offset** depends on the **CPU load** and is **close to linear** characteristics



Static vs. Short Bursts CPU Load (Dell R750)



We compared the PC measurements under **static CPU load**, at 50% CPU load, against the **short bursts:** to achieve 50% CPU load, in 10s cycles → 5s of 100% CPU load, then 5s of 0% CPU load



Conclusions



Conclusions





Different standardization bodies address distinct aspects of energy saving, and there is a need for a unified E2E EE testing framework



The main challenges are related to the standardized methodologies for the VNFs, and various deployment configurations for O-RAN components



New metrics and benchmarks are essential to the framework. They should take into account both the energy-saving and QoS/performance goals



The framework's design and execution will involve developing a standardized core testing procedure adaptable to various scenarios.



The initial focus will be on the Component-level measurements for EE and Global/feature based testing for EE - they are feasible for a lab environment



Power consumption measurements for a consumer Laptop and a Dell Server were conducted under a static CPU load forced by a third-party APP.




The gap between Kepler and the Electric Socket follows an almost linear function.



The next steps cover power consumption measurements of individual PODs, e.g., measurements for RIC and xApps operating under the simulated RAN environment.

White paper





White paper QR code



https://www.i14y-lab.com/article/i14y-lab-energy-efficiency-testing-framework-white-paper





Meet Rimedo Labs at the Marketplace!

#SUMMIT25 · SEPTEMBER 2025







Special Thanks







Your trusted partner in: O-RAN, 5G & Beyond, Private Mobile Networks.

Let's keep in touch!

RIMEDO Labs

ul. Polanka 3 61-131 Poznan, Poland

info@rimedolabs.com

rimedolabs.com



The information contained herein is the property of RIMEDO and is provided only if it is not disclosed, directly or indirectly to a third party, or used for purposes other than those for which it was prepared.

ETSI is the copyright holder of LTE, LTE-Advanced and LTE Advanced Pro and 5G Logos. LTE is a trade mark of ETSI. RIMEDO is authorized to use the LTE, LTE-Advanced, LTE-Advanced Pro and 5G logos and the acronym LTE.

All information discussed in the document is provided "as is" and RIMEDO makes no warranty that this information is fit for purpose. Users use this information at their own risk and responsibility.

© 2025 RIMEDO sp. z o. o. All rights reserved.